



## NOTES

1. Refer to the City of Fullerton's Approved Materials List for approved manufacturers and model numbers.
2. Contact the Water Engineering Division for the type of 1½" or 2" meter required.
3. The water service shall extend perpendicular to street center line except in cul-de-sacs, and the tap shall be at least 24" from any adjacent joint or service.
4. Meter register to be set for curbside reading.
5. A traffic load rating cover shall be used in areas without curb, in areas with rolled curb, or where the meter is located within 7' of the BCR, ECR or a driveway approach.
6. Meter box cover to be flush with the finished grade in concrete, and ½" above grade in landscaped areas. Meter boxes shall be a minimum of 8" clear from adjacent meter boxes, and 7' clear from top of "X" of driveway approaches and sidewalk access ramp.
7. For domestic/fire combination service installations, a check valve to be installed on-site as instructed by the Building Inspector or Fire Inspector.
8. Water meter to be supplied by City of Fullerton, as determined by City Engineer.
9. Water meter to be installed per manufacturer's requirements.
10. Water meter and meter box shall be installed perpendicular to the curb, or as determined by City Engineer.

## 1½" & 2" WATER METER INSTALLATION



REVISIONS			
NO.	DATE	NO.	DATE
1	12/01/00	4	02/28/17
2	02/11/13	5	09/24/19
3	02/29/16	6	04/20/22

  
CITY ENGINEER      5/9/2022  
DATE

  
PUBLIC WORKS DIRECTOR      5/24/2022  
DATE

STANDARD DETAIL

602

SHEET 2 OF 2

DEPARTMENT OF PUBLIC WORKS